



The LS454 is a luminaire designed for use in external ceiling areas where a recessed downlight is not practical. As an IP67 rated luminaire, the protection against water ingress is excellent, making it suitable for use in exterior applications. In both LED and Halogen variants, the light output is diffused.



LED version see page 151.

### SPECIFICATIONS

Lamp Source	Halogen Bi-pin / QT12 (GY6.35)	20 W IRC
IP Rating	IP67	
Construction	Powder coated aluminium	
	<ul style="list-style-type: none"> <li>■ Black</li> <li>■ Silver</li> <li>■ Superchrome</li> </ul>	
Installation Type	Surface ceiling mount	
Standard Inclusions	Thermal cutout Toughened diffuser lens	
Ambient Operating Temperature	-20 °C to +50 °C	
Warranty	2 year structural, 1 year electrical	
Accessories	LSTE6-2 Integral transformer	
Photometrics	Go to <a href="http://www.lumascape.com.au">www.lumascape.com.au</a> ▶ Technical Data ▶ Photometric Files	



LS454A Aura



NOTE: Product specifications are subject to change without notice. Any luminaire can become hot - take care with appropriate use and placement.

### CONFIGURE THIS PRODUCT >

LS454	→	A	→				
<b>LED SOURCE</b>			<b>FINISH</b>				
Lamp	Wattage	Base	Voltage	Code	Description	Material	Code
Halogen Bi-pin / QT12	20 W IRC max	GY6.35	12 V AC <sup>(1)</sup>	A	Powder coated black	Aluminium	CB
					Powder coated anodic silver	Aluminium	CS
					Powder coated Superchrome	Aluminium	CA

<sup>(1)</sup> Requires integral LSTE6-2 or remote transformer - see page 239.